

जीवाजी विश्वविद्यालय, ग्वालियर

online

कोटेशन आमंत्रण पत्र

क्रमांक/ एफ.जे.यू./यंत्रि/2021/324

दिनांक: - 27 / 12 / 2021

प्रति,

विषय : - जीवाजी विश्वविद्यालय के आवास क्रमांक एच.आई.जी.-05 के रसोई एवं वाथरूम में पी.व्ही.सी डोर शटर फ्रेम सहित एवं एल्युमीनियम विण्डों का कार्य कराये जाने बावत् महोदय,

जीवाजी विश्वविद्यालय के आवास क्रमांक एच.आई.जी.-05 के रसोई एवं वाथरूम में पी.व्ही.सी डोर शटर फ्रेम सहित एवं एल्युमीनियम विण्डों का कार्य कराये जाने हेतु दरें आमंत्रित की जाती हैं. कृपया अपनी दरें दिनांक 10-01-2022 तक सील बंद लिफाफे के द्वारा कुलसचिव जीवाजी विश्वविद्यालय ग्वालियर के पते पर भेजे। लिफाफे पर कुटेशन, कार्य का नाम तथा अंतिम तिथि आवश्यक रूप से अंकित करें।

सं. क्र.	एस.ओ.आर.क्रमांक	विवरण	मात्रा	दर
01	9.124.1	Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete. With 2nd class teak wood beading 62x19 mm.	2.00 sqm	
02	9.169.2	Providing and fixing factory made single extruded WPC(Wood Polymer Composite) solid door/window/ceostory windows and other frames/chowkhat comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice .husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) fabricated with miter joints after applying PVC solvent cement and screwed with full body threaded star headed S.S. screws having minimum density of 750 kg/m ³ and screw withdrawal strength of 2200 N (Face) & 900 N (Edge), minimum compressive strength 58.N/mm ² , modulus of elasticity 900 N/mm ² and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S. hold fast/lugs/S.S.dash fasteners of required dia and length complete as per direction	9.85 rm	

		of Engineer-in-Charge. (M.S. hold fast/lugs or S.S. dash fasteners shall be paid Single rebate (100 mm X50 mm)		
03.	9.170.1	Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice .husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm ² , modulus of elasticity 850 N/mm ² and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-InCharge. (Note: stainless steel butt hinges and necessary S.S screws shall be paid 24 mm thick WPC (Wood polymer composite) solid plain flush door shutter	3.00 sqm	
04.	10.5.1	Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x5mm angle iron and 3mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. Using M.S. angels 40x40x6mm for diagonal braces	1.85 sqm	
05	13.1.2	12 mm cement plaster of mix : 1:6 (1 cement : 6 sand)	3.00 sqm	
06.	15.15.1	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead: Of area 3 sq. metres and below.	03 Nos	
07.	21.1.2.2	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all	15.00 k.g	

		complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : Powder coated aluminium (minimum thickness of powder coating 50 micron)		
08.	21.3.1	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item) : With float glass panes of 4.0 mm thickness (weight not less than 10 kg/sqm)	3.50 sqm	

शर्तें :-

- 1- सामाग्री की मात्रा आवश्यकतानुसार घटाई व बढ़ाई जा सकती है।
- 2- फर्म के नाम पैन नम्बर/टिन नम्बर/जी.एस.टी.नम्बर होना आवश्यक है।
- 3- कुटेशन स्वीकृत/अस्वीकृत करने का अधिकार कुलसचिव विश्वविद्यालय के पास सुरक्षित रहेगा।
- 4- कुटेशन अंतिम तिथि तक वि.वि. में प्राप्त होना आवश्यक है।
- 5- लिफाफे पर कार्य का नाम अंकित होना चाहिये।


कुलसचिव